

442 Appendices

443 The following appendices provide additional details that are relevant to the paper. Appendices [A](#)
444 and [B](#) explain any tasks related to Energy-Based Modelling and Predictive Uncertainty Quantification
445 through Conformal Prediction, respectively. Appendix [C](#) provides additional technical and implemen-
446 tation details about our proposed generator, *ECCCo*, including references to our open-sourced code
447 base. A complete overview of our experimental setup detailing our parameter choices, training proce-
448 dures and initial black-box model performance can be found in Appendix [D](#). Finally, Appendix [E](#)
449 reports all of our experimental results in more detail.

450 A Energy-Based Modelling

451 Since we were not able to identify any existing open-source software for Energy-Based Modelling
452 that would be flexible enough to cater to our needs, we have developed a Julia package from scratch.
453 The package has been open-sourced, but to avoid compromising the double-blind review process, we
454 refrain from providing more information at this stage. In our development we have heavily drawn on
455 the existing literature: Du and Mordatch [\[25\]](#) describe best practices for using EBM for generative
456 modelling; Grathwohl et al. [\[24\]](#) explain how EBM can be used to train classifiers jointly for the
457 discriminative and generative tasks. We have used the same package for training and inference, but
458 there are some important differences between the two cases that are worth highlighting here.

459 A.1 Training: Joint Energy Models

460 To train our Joint Energy Models we broadly follow the approach outlined in Grathwohl et al. [\[24\]](#).
461 These models are trained to optimize a hybrid objective that involves a standard classification loss
462 component $L_{\text{clf}}(\theta) = -\log p_{\theta}(\mathbf{y}|\mathbf{x})$ (e.g. cross-entropy loss) as well as a generative loss component
463 $L_{\text{gen}}(\theta) = -\log p_{\theta}(\mathbf{x})$.

464 To draw samples from $p_{\theta}(\mathbf{x})$, we rely exclusively on the conditional sampling approach described
465 in Grathwohl et al. [\[24\]](#) for both training and inference: we first draw $\mathbf{y} \sim p(\mathbf{y})$ and then sample
466 $\mathbf{x} \sim p_{\theta}(\mathbf{x}|\mathbf{y})$ [\[24\]](#) via Equation [2](#) with energy $\mathcal{E}(\mathbf{x}|\mathbf{y}) = \mu_{\theta}(\mathbf{x})[\mathbf{y}]$ where $\mu_{\theta} : \mathcal{X} \mapsto \mathbb{R}^K$ returns
467 the linear predictions (logits) of our classifier M_{θ} . While our package also supports unconditional
468 sampling, we found conditional sampling to work well. It is also well aligned with CE, since in this
469 context we are interested in conditioning on the target class.

470 As mentioned in the body of the paper, we rely on a biased sampler involving separately specified
471 values for the step size ϵ and the standard deviation σ of the stochastic term involving \mathbf{r} . Formally,
472 our biased sampler performs updates as follows:

$$\hat{\mathbf{x}}_{j+1} \leftarrow \hat{\mathbf{x}}_j - \frac{\epsilon}{2} \mathcal{E}(\hat{\mathbf{x}}_j|\mathbf{y}^+) + \sigma \mathbf{r}_j, \quad j = 1, \dots, J \quad (7)$$

473 Consistent with Grathwohl et al. [\[24\]](#), we have specified $\epsilon = 2$ and $\sigma = 0.01$ as the default values for
474 all of our experiments. The number of total SGLD steps J varies by dataset ([Table 3](#)). Following best
475 practices, we initialize \mathbf{x}_0 randomly in 5% of all cases and sample from a buffer in all other cases.
476 The buffer itself is randomly initialised and gradually grows to a maximum of 10,000 samples during
477 training as $\hat{\mathbf{x}}_J$ is stored in each epoch [\[25, 24\]](#).

478 It is important to realise that sampling is done during each training epoch, which makes training Joint
479 Energy Models significantly harder than conventional neural classifiers. In each epoch the generated
480 (batch of) sample(s) $\hat{\mathbf{x}}_J$ is used as part of the generative loss component, which compares its energy
481 to that of observed samples \mathbf{x} : $L_{\text{gen}}(\theta) = \mu_{\theta}(\mathbf{x})[\mathbf{y}] - \mu_{\theta}(\hat{\mathbf{x}}_J)[\mathbf{y}]$. Our full training objective can be
482 summarized as follows,

$$L(\theta) = L_{\text{clf}}(\theta) + L_{\text{gen}}(\theta) + \lambda L_{\text{reg}}(\theta) \quad (8)$$

483 where $L_{\text{reg}}(\theta)$ is a Ridge penalty (L2 norm) that regularises energy magnitudes for both observed and
484 generated samples [\[25\]](#). We have used varying degrees of regularization depending on the dataset (λ
485 in [Table 3](#)).

486 Contrary to existing work, we have not typically used the entire minibatch of training data for the
487 generative loss component but found that using a subset of the minibatch was often sufficient in

Table 3: EBM hyperparameter choices for our experiments.

Dataset	SGLD Steps	Batch Size	λ
Linearly Separable	30	50	0.10
Moons	30	10	0.10
Circles	20	100	0.01
MNIST	25	10	0.01
GMSC	30	10	0.10

JEM Ensemble




Figure 3: Conditionally generated *MNIST* images for our JEM Ensemble.

488 attaining decent generative performance (Table 3). This has helped to reduce the computational
 489 burden for our models, which should make it easier for others to reproduce our findings. Figures 3
 490 and 4 show generated samples for our *MNIST* and *Moons* data, to provide a sense of their generative
 491 property.

492 A.2 Inference: Quantifying Models’ Generative Property

493 At inference time, we assume no prior knowledge about the model’s generative property. This means
 494 that we do not tap into the existing buffer of generated samples for our Joint Energy Models, but
 495 instead generate conditional samples from scratch. While we have relied on the default values $\epsilon = 2$
 496 and $\sigma = 0.01$ also during inference, the number of total SGLD steps was set to $J = 500$ in all cases,
 497 so significantly higher than during training. For all of our synthetic datasets and models, we generated
 498 50 conditional samples and then formed subsets containing the $n_E = 25$ lowest-energy samples.
 499 While in practice it would be sufficient to do this once for each model and dataset, we have chosen
 500 to perform sampling separately for each individual counterfactual in our experiments to account for
 501 stochasticity. To help reduce the computational burden for our real-world datasets we have generated
 502 only 10 conditional samples each time and used all of them in our counterfactual search. Using more
 503 samples, as we originally did, had no substantial impact on our results.




Figure 4: Conditionally generated samples (stars) for our *Moons* data using a JEM.

504 B Conformal Prediction

505 In this Appendix [B](#) we provide some more background on CP and explain in some more detail how
 506 we have used recent advances in Conformal Training for our purposes.

507 B.1 Background on CP

508 Intuitively, CP works under the premise of turning heuristic notions of uncertainty into rigorous
 509 uncertainty estimates by repeatedly sifting through the data. It can be used to generate prediction
 510 intervals for regression models and prediction sets for classification models. Since the literature on
 511 CE and AR is typically concerned with classification problems, we focus on the latter. A particular
 512 variant of CP called Split Conformal Prediction (SCP) is well-suited for our purposes, because it
 513 imposes only minimal restrictions on model training.

514 Specifically, SCP involves splitting the data $\mathcal{D}_n = \{(\mathbf{x}_i, \mathbf{y}_i)\}_{i=1, \dots, n}$ into a proper training set $\mathcal{D}_{\text{train}}$
 515 and a calibration set \mathcal{D}_{cal} . The former is used to train the classifier in any conventional fashion.
 516 The latter is then used to compute so-called nonconformity scores: $\mathcal{S} = \{s(\mathbf{x}_i, \mathbf{y}_i)\}_{i \in \mathcal{D}_{\text{cal}}}$ where
 517 $s : (\mathcal{X}, \mathcal{Y}) \mapsto \mathbb{R}$ is referred to as *score function*. In the context of classification, a common choice for
 518 the score function is just $s_i = 1 - M_\theta(\mathbf{x}_i)[\mathbf{y}_i]$, that is one minus the softmax output corresponding
 519 to the observed label \mathbf{y}_i [\[28\]](#).

520 Finally, classification sets are formed as follows,

$$C_\theta(\mathbf{x}_i; \alpha) = \{\mathbf{y} : s(\mathbf{x}_i, \mathbf{y}) \leq \hat{q}\} \quad (9)$$

521 where \hat{q} denotes the $(1 - \alpha)$ -quantile of \mathcal{S} and α is a predetermined error rate. As the size of the
 522 calibration set increases, the probability that the classification set $C(\mathbf{x}_{\text{test}})$ for a newly arrived sample
 523 \mathbf{x}_{test} does not cover the true test label \mathbf{y}_{test} approaches α [\[28\]](#).

524 Observe from Equation [9](#) that Conformal Prediction works on an instance-level basis, much like CE
 525 are local. The prediction set for an individual instance \mathbf{x}_i depends only on the characteristics of that
 526 sample and the specified error rate. Intuitively, the set is more likely to include multiple labels for
 527 samples that are difficult to classify, so the set size is indicative of predictive uncertainty. To see why
 528 this effect is exacerbated by small choices for α consider the case of $\alpha = 0$, which requires that the
 529 true label is covered by the prediction set with probability equal to 1.

530 B.2 Differentiability

531 The fact that conformal classifiers produce set-valued predictions introduces a challenge: it is not
 532 immediately obvious how to use such classifiers in the context of gradient-based counterfactual
 533 search. Put differently, it is not clear how to use prediction sets in Equation [1](#). Fortunately, Stutz et al.
 534 [\[30\]](#) have recently proposed a framework for Conformal Training that also hinges on differentiability.
 535 Specifically, they show how Stochastic Gradient Descent can be used to train classifiers not only
 536 for the discriminative task but also for additional objectives related to Conformal Prediction. One
 537 such objective is *efficiency*: for a given target error rate α , the efficiency of a conformal classifier




Figure 5: Prediction set size (left), smooth set size loss (centre) and configurable classification loss (right) for a JEM trained on our *Linearly Separable* data.

538 improves as its average prediction set size decreases. To this end, the authors introduce a smooth set
 539 size penalty defined in Equation [6] in the body of this paper. Formally, it is defined as $C_{\theta, \mathbf{y}}(\mathbf{x}_i; \alpha) :=$
 540 $\sigma((s(\mathbf{x}_i, \mathbf{y}) - \alpha)T^{-1})$ for $\mathbf{y} \in \mathcal{Y}$, where σ is the sigmoid function and T is a hyper-parameter used
 541 for temperature scaling [30].

542 In addition to the smooth set size penalty, Stutz et al. [30] also propose a configurable classification
 543 loss function, that can be used to enforce coverage. For *MNIST* data, we found that using this
 544 function generally improved the visual quality of the generated counterfactuals, so we used it
 545 in our experiments involving real-world data. For the synthetic dataset, visual inspection of the
 546 counterfactuals showed that using the configurable loss function sometimes led to overshooting:
 547 counterfactuals would end up deep inside the target domain but far away from the observed samples.
 548 For this reason, we instead relied on standard cross-entropy loss for our synthetic datasets. As we have
 549 noted in the body of the paper, more experimental work is certainly needed in this context. Figure [5]
 550 shows the prediction set size (left), smooth set size loss (centre) and configurable classification loss
 551 (right) for a JEM trained on our *Linearly Separable* data.

552 C ECCCo

553 In this section, we briefly discuss convergence conditions for CE and provide details concerning the
 554 actual implementation of our framework in Julia.

555 C.1 A Note on Convergence

556 Convergence is not typically discussed much in the context of CE, even though it has important
 557 implications on outcomes. One intuitive way to specify convergence is in terms of threshold
 558 probabilities: once the predicted probability $p(\mathbf{y}^+|\mathbf{x}')$ exceeds some user-defined threshold γ such
 559 that the counterfactual is valid, we could consider the search to have converged. In the binary case,
 560 for example, convergence could be defined as $p(\mathbf{y}^+|\mathbf{x}') > 0.5$ in this sense. Note, however, how
 561 this can be expected to yield counterfactuals in the proximity of the decision boundary, a region
 562 characterized by high aleatoric uncertainty. In other words, counterfactuals generated in this way
 563 would generally not be plausible. To avoid this from happening, we specify convergence in terms of
 564 gradients approaching zero for all our experiments and all of our generators. This allows us to get
 565 a cleaner read on how the different counterfactual search objectives affect counterfactual outcomes.

566 C.2 ECCCo.jl

567 The core part of our code base is integrated into a larger ecosystem of Julia packages that we
 568 are actively developing and maintaining. To avoid compromising the double-blind review process,
 569 we only provide a link to an anonymized repository at this stage: [https://anonymous.4open](https://anonymous.4open.science/r/ECCCo-1252/README.md)
 570 [science/r/ECCCo-1252/README.md](https://anonymous.4open.science/r/ECCCo-1252/README.md).

571 D Experimental Setup

572 Table [4] provides an overview of all parameters related to our experiments. The *GMSC* data were
 573 randomly undersampled for balancing purposes and all features were standardized. *MNIST* data was
 574 also randomly undersampled for reasons outlined below. Pixel values were preprocessed to fall in the
 575 range of $[-1, 1]$ and a small Gaussian noise component ($\sigma = 0.03$) was added to training samples

Table 4: Parameter choices for our experiments.

Dataset	Sample Size	Network Architecture				Training	
		Hidden Units	Hidden Layers	Activation	Ensemble Size	Epochs	Batch Size
Linearly Separable	1000	16	3	swish	5	100	100
Moons	2500	32	3	relu	5	500	128
Circles	1000	32	3	swish	5	100	100
MNIST	10000	128	1	swish	5	100	128
GMSC	13370	128	2	swish	5	100	250

Table 5: Various standard performance metrics for our different models grouped by dataset.

Dataset	Model	Performance Metrics		
		Accuracy	Precision	F1-Score
Linearly Separable	JEM	0.99	0.99	0.99
	MLP	0.99	0.99	0.99
Moons	JEM	1.00	1.00	1.00
	MLP	1.00	1.00	1.00
Circles	JEM	0.98	0.98	0.98
	MLP	1.00	1.00	1.00
MNIST	JEM	0.83	0.84	0.83
	JEM Ensemble	0.90	0.90	0.89
	MLP	0.95	0.95	0.95
	MLP Ensemble	0.95	0.95	0.95
GMSC	JEM	0.73	0.75	0.73
	JEM Ensemble	0.73	0.75	0.73
	MLP	0.75	0.75	0.75
	MLP Ensemble	0.75	0.75	0.75

576 following common practice in the EBM literature. All of our models were trained through mini-batch
 577 training using the Adam optimiser (Kingma and Ba [37]). Table 5 shows standard evaluation metrics
 578 measuring the predictive performance of our different models grouped by dataset. These measures
 579 were computed on test data.

580 Table 6 summarises our hyperparameter choices for the counterfactual generators where η denotes
 581 the learning rate used for Stochastic Gradient Descent (SGD) and $\lambda_1, \lambda_2, \lambda_3$ represent the chosen
 582 penalty strengths (Equations 1 and 5). Here λ_1 also refers to the chosen penalty for the distance from
 583 factual values that applies to both *Wachter* and *REVISE*, but not *Schut* which is penalty-free. *Schut* is
 584 also the only generator that uses JSMA instead of SGD for optimization.

585 D.1 Compute

586 To enable others to easily replicate our experiments, we have chosen to work with small neural
 587 network architectures and randomly undersampled the *MNIST* dataset (maintaining class balance).
 588 All of our experiments could then be run locally on a personal machine. The longest runtimes we

Table 6: Generator hyperparameters.

Dataset	η	λ_1	λ_2	λ_3
Linearly Separable	0.01	0.25	0.75	0.75
Moons	0.05	0.25	0.75	0.75
Circles	0.01	0.25	0.75	0.75
MNIST	0.10	0.10	0.25	0.25
GMSC	0.05	0.10	0.50	0.50

589 experienced for model training and counterfactual benchmarking were on the order of 8-12 hours
590 (*MNIST* data). For the synthetic data, all experiments could be completed in less than an hour.

591 We have summarised our system information below:

592 **Software:**

- 593 • System Version: macOS 13.3.1
- 594 • Kernel Version: Darwin 22.4.0

595 **Hardware:**

- 596 • Model Name: MacBook Pro
- 597 • Model Identifier: MacBookPro16,1
- 598 • Processor Name: 8-Core Intel Core i9
- 599 • Processor Speed: 2.3 GHz
- 600 • Number of Processors: 1
- 601 • Total Number of Cores: 8
- 602 • L2 Cache (per Core): 256 KB
- 603 • L3 Cache: 16 MB
- 604 • Hyper-Threading Technology: Enabled
- 605 • Memory: 32 GB

606 **E Results**

607 Figure 6 shows examples of counterfactuals for *MNIST* data where the underlying model is our *JEM*
608 *Ensemble*. Original images are shown on the diagonal and the corresponding counterfactuals are
609 plotted across rows.

610 Table 7 reports all of the evaluation metrics we have computed. Table 8 reports the same metrics
611 for the subset of valid counterfactuals. The ‘Unfaithfulness’ and ‘Implausibility’ metrics have been
612 discussed extensively in the body of the paper. The ‘Cost’ metric relates to the distance between
613 the factual and the counterfactual. The ‘Redundancy’ metric measures sparsity in is defined as the
614 percentage of features that remain unperturbed (higher is better). The ‘Uncertainty’ metric is just
615 the average value of the smooth set size penalty (Equation 6). Finally, ‘Validity’ is the percentage of
616 valid counterfactuals.

Table 7: All results for all datasets: sample averages +/- one standard deviation over all counterfactuals. Best outcomes are highlighted in bold. Asterisks indicate that the given value is more than one (*) or two (**) standard deviations away from the baseline (Wachter).

Model	Data	Generator	Cost ↓	Unfaithfulness ↓	Implausibility ↓	Redundancy ↑	Uncertainty ↓	Validity ↑	
Circles	JEM	ECCCo	0.74 ± 0.21	0.52 ± 0.36	1.22 ± 0.46	0.00 ± 0.00	0.00 ± 0.00	1.00 ± 0.00**	
		ECCCo (no CP)	0.72 ± 0.21	0.54 ± 0.39	1.21 ± 0.46	0.00 ± 0.00	0.00 ± 0.00	1.00 ± 0.00**	
		ECCCo (no EBM)	0.52 ± 0.15	0.70 ± 0.33	1.30 ± 0.37	0.00 ± 0.00	0.00 ± 0.00	1.00 ± 0.00**	
		REVISE	0.97 ± 0.34	0.48 ± 0.16*	0.95 ± 0.32*	0.00 ± 0.00	0.00 ± 0.00	0.50 ± 0.51	
		Schut	1.06 ± 0.43	0.54 ± 0.43	1.28 ± 0.53	0.26 ± 0.25*	0.00 ± 0.00	1.00 ± 0.00**	
		Wachter	0.44 ± 0.16	0.68 ± 0.34	1.33 ± 0.32	0.00 ± 0.00	0.00 ± 0.00	0.98 ± 0.14	
	MLP	ECCCo	0.67 ± 0.19	0.65 ± 0.53	1.17 ± 0.41	0.00 ± 0.00	0.09 ± 0.19**	1.00 ± 0.00	
		ECCCo (no CP)	0.71 ± 0.16	0.49 ± 0.35	1.19 ± 0.44	0.00 ± 0.00	0.05 ± 0.16**	1.00 ± 0.00	
		ECCCo (no EBM)	0.45 ± 0.11	0.84 ± 0.51	1.23 ± 0.31	0.00 ± 0.00	0.15 ± 0.23*	1.00 ± 0.00	
		REVISE	0.96 ± 0.31	0.58 ± 0.52	0.95 ± 0.32	0.00 ± 0.00	0.00 ± 0.00**	0.50 ± 0.51	
		Schut	0.57 ± 0.11	0.58 ± 0.37	1.23 ± 0.43	0.43 ± 0.18**	0.00 ± 0.00**	1.00 ± 0.00	
		Wachter	0.40 ± 0.09	0.83 ± 0.50	1.24 ± 0.29	0.00 ± 0.00	0.53 ± 0.01	1.00 ± 0.00	
GMSC	JEM	ECCCo	17.45 ± 2.92**	79.16 ± 11.67**	18.26 ± 4.92**	0.00 ± 0.00	0.10 ± 0.01	1.00 ± 0.00	
		REVISE	3.43 ± 1.67**	186.40 ± 28.06	5.34 ± 2.38**	0.00 ± 0.00	0.51 ± 0.22	1.00 ± 0.00	
		Schut	1.27 ± 0.33**	200.98 ± 28.49	6.50 ± 2.01**	0.77 ± 0.07**	0.07 ± 0.00	1.00 ± 0.00	
		Wachter	57.71 ± 0.47	214.08 ± 45.35	61.04 ± 2.58	0.00 ± 0.00	0.07 ± 0.00	1.00 ± 0.00	
	JEM Ensemble	ECCCo	17.43 ± 3.04**	83.28 ± 13.26**	17.21 ± 4.46**	0.00 ± 0.00	0.16 ± 0.11	1.00 ± 0.00	
		REVISE	2.94 ± 1.13**	194.24 ± 35.41	4.95 ± 1.26**	0.00 ± 0.00	0.51 ± 0.29	1.00 ± 0.00	
		Schut	1.03 ± 0.20**	208.45 ± 34.60	6.12 ± 1.91**	0.85 ± 0.05**	0.09 ± 0.04	1.00 ± 0.00	
		Wachter	56.79 ± 44.68	186.19 ± 33.88	60.70 ± 44.32	0.00 ± 0.00	0.07 ± 0.00	1.00 ± 0.00	
	MLP	ECCCo	17.05 ± 2.87**	75.93 ± 14.27**	17.20 ± 3.15**	0.00 ± 0.00	0.19 ± 0.08	1.00 ± 0.00**	
		REVISE	2.93 ± 1.24**	196.75 ± 41.25	4.84 ± 0.60**	0.00 ± 0.00	0.38 ± 0.18	1.00 ± 0.00**	
		Schut	1.49 ± 0.87**	212.00 ± 41.15	6.44 ± 1.34**	0.77 ± 0.13**	0.12 ± 0.01	1.00 ± 0.00**	
		Wachter	42.97 ± 39.50	218.34 ± 53.26	45.84 ± 39.39	0.00 ± 0.00	0.06 ± 0.06	0.50 ± 0.51	
	MLP Ensemble	ECCCo	16.63 ± 2.62**	73.86 ± 14.63**	17.92 ± 4.17**	0.00 ± 0.00	0.23 ± 0.07	1.00 ± 0.00**	
		REVISE	3.73 ± 2.36**	207.21 ± 43.20	5.78 ± 2.10**	0.00 ± 0.00	0.33 ± 0.19	1.00 ± 0.00**	
		Schut	1.20 ± 0.47**	205.36 ± 32.11	7.00 ± 2.15**	0.79 ± 0.09**	0.12 ± 0.01	1.00 ± 0.00**	
		Wachter	69.30 ± 66.00	213.71 ± 54.17	73.09 ± 64.50	0.00 ± 0.00	0.06 ± 0.06	0.50 ± 0.51	
	Linearly Separable	JEM	ECCCo	0.75 ± 0.17	0.03 ± 0.06**	0.20 ± 0.08**	0.00 ± 0.00	0.00 ± 0.00	1.00 ± 0.00
			ECCCo (no CP)	0.75 ± 0.17	0.03 ± 0.06**	0.20 ± 0.08**	0.00 ± 0.00	0.00 ± 0.00	1.00 ± 0.00
ECCCo (no EBM)			0.70 ± 0.16	0.16 ± 0.11	0.34 ± 0.19	0.00 ± 0.00	0.00 ± 0.00	1.00 ± 0.00	
REVISE			0.41 ± 0.15	0.19 ± 0.03	0.41 ± 0.01**	0.00 ± 0.00	0.36 ± 0.36	0.50 ± 0.51	
Schut			1.15 ± 0.35	0.39 ± 0.07	0.73 ± 0.17	0.25 ± 0.25	0.00 ± 0.00	1.00 ± 0.00	
Wachter			0.50 ± 0.13	0.18 ± 0.10	0.44 ± 0.17	0.00 ± 0.00	0.00 ± 0.00	1.00 ± 0.00	
MLP		ECCCo	0.95 ± 0.16	0.29 ± 0.05**	0.23 ± 0.06**	0.00 ± 0.00	0.00 ± 0.00**	1.00 ± 0.00	
		ECCCo (no CP)	0.94 ± 0.16	0.29 ± 0.05**	0.23 ± 0.07**	0.00 ± 0.00	0.00 ± 0.00**	1.00 ± 0.00	
		ECCCo (no EBM)	0.60 ± 0.15	0.46 ± 0.05	0.28 ± 0.04**	0.00 ± 0.00	0.02 ± 0.10**	1.00 ± 0.00	
		REVISE	0.42 ± 0.14	0.56 ± 0.05	0.41 ± 0.01	0.00 ± 0.00	0.47 ± 0.50	0.48 ± 0.50	
		Schut	0.77 ± 0.17	0.43 ± 0.06*	0.47 ± 0.36	0.20 ± 0.25	0.00 ± 0.00**	1.00 ± 0.00	
		Wachter	0.51 ± 0.15	0.51 ± 0.04	0.40 ± 0.08	0.00 ± 0.00	0.59 ± 0.02	1.00 ± 0.00	
MNIST		JEM	ECCCo	334.61 ± 46.37	19.28 ± 5.01**	314.76 ± 32.36*	0.00 ± 0.00	4.43 ± 0.56	0.98 ± 0.12
			REVISE	170.68 ± 63.26	188.70 ± 26.18*	255.26 ± 41.50**	0.00 ± 0.00	4.39 ± 0.91	0.96 ± 0.20
			Schut	9.44 ± 1.60**	211.00 ± 27.21	286.61 ± 39.85*	0.99 ± 0.00**	1.08 ± 1.95*	0.24 ± 0.43
			Wachter	128.36 ± 14.95	222.90 ± 26.56	361.88 ± 39.74	0.00 ± 0.00	4.37 ± 0.98	0.95 ± 0.21
		JEM Ensemble	ECCCo	342.64 ± 41.14	15.99 ± 3.06**	294.72 ± 30.75**	0.00 ± 0.00	2.07 ± 0.06**	1.00 ± 0.00**
			REVISE	170.21 ± 58.02	173.59 ± 20.65**	246.32 ± 37.46**	0.00 ± 0.00	2.56 ± 0.83	0.93 ± 0.26
	Schut		9.78 ± 1.02**	205.33 ± 24.07	287.39 ± 39.33*	0.99 ± 0.00**	0.32 ± 0.94**	0.11 ± 0.31	
	Wachter		135.07 ± 16.79	217.67 ± 23.78	363.23 ± 39.24	0.00 ± 0.00	2.93 ± 0.77	0.94 ± 0.23	
	MLP	ECCCo	605.17 ± 44.78	41.95 ± 6.50**	591.58 ± 36.24	0.00 ± 0.00	0.57 ± 0.00**	1.00 ± 0.00**	
		REVISE	146.61 ± 36.96	365.82 ± 15.35*	249.49 ± 41.55**	0.00 ± 0.00	0.62 ± 0.30	0.87 ± 0.34	
		Schut	9.95 ± 0.37**	382.44 ± 17.81	285.98 ± 42.48*	0.99 ± 0.00**	0.05 ± 0.19**	0.06 ± 0.24	
		Wachter	136.08 ± 16.09	386.05 ± 16.60	361.83 ± 42.18	0.00 ± 0.00	0.68 ± 0.36	0.84 ± 0.36	
MLP Ensemble	ECCCo	525.87 ± 34.00	31.43 ± 3.91**	490.88 ± 27.19	0.00 ± 0.00	0.29 ± 0.00**	1.00 ± 0.00**		
	REVISE	146.60 ± 35.64	337.74 ± 11.89*	247.67 ± 38.36**	0.00 ± 0.00	0.39 ± 0.22	0.85 ± 0.36		
	Schut	9.98 ± 0.25**	359.54 ± 14.52	283.99 ± 41.08*	0.99 ± 0.00**	0.03 ± 0.14**	0.06 ± 0.24		
	Wachter	137.53 ± 18.95	360.79 ± 14.39	357.73 ± 42.55	0.00 ± 0.00	0.47 ± 0.64	0.80 ± 0.40		
Moons	JEM	ECCCo	1.56 ± 0.44	0.31 ± 0.30*	1.20 ± 0.15**	0.00 ± 0.00	0.00 ± 0.00**	1.00 ± 0.00**	
		ECCCo (no CP)	1.56 ± 0.46	0.37 ± 0.30*	1.21 ± 0.17**	0.00 ± 0.00	0.00 ± 0.00**	1.00 ± 0.00**	
		ECCCo (no EBM)	0.80 ± 0.25	0.91 ± 0.32	1.71 ± 0.25	0.00 ± 0.00	0.00 ± 0.00**	1.00 ± 0.00**	
		REVISE	1.04 ± 0.43	0.78 ± 0.23	1.57 ± 0.26	0.00 ± 0.00	0.00 ± 0.00**	1.00 ± 0.00**	
		Schut	1.12 ± 0.31	0.67 ± 0.27	1.50 ± 0.22*	0.08 ± 0.19	0.00 ± 0.00**	0.98 ± 0.14	
		Wachter	0.72 ± 0.24	0.80 ± 0.27	1.78 ± 0.24	0.00 ± 0.00	0.02 ± 0.10	0.98 ± 0.14	
	MLP	ECCCo	2.18 ± 1.05	0.80 ± 0.62	1.69 ± 0.40	0.00 ± 0.00	0.15 ± 0.24*	1.00 ± 0.00	
		ECCCo (no CP)	2.07 ± 1.15	0.79 ± 0.62	1.68 ± 0.42	0.00 ± 0.00	0.15 ± 0.24*	1.00 ± 0.00	
		ECCCo (no EBM)	1.25 ± 0.92	1.34 ± 0.47	1.68 ± 0.47	0.00 ± 0.00	0.43 ± 0.18	1.00 ± 0.00	
		REVISE	0.79 ± 0.19*	1.45 ± 0.44	1.64 ± 0.31	0.00 ± 0.00	0.40 ± 0.22	1.00 ± 0.00	
		Schut	0.73 ± 0.25*	1.45 ± 0.55	1.73 ± 0.48	0.31 ± 0.28*	0.00 ± 0.00**	0.90 ± 0.30	
		Wachter	1.08 ± 0.83	1.32 ± 0.41	1.69 ± 0.32	0.00 ± 0.00	0.52 ± 0.08	1.00 ± 0.00	

Table 8: All results for all datasets: sample averages +/- one standard deviation over all valid counterfactuals. Best outcomes are highlighted in bold. Asterisks indicate that the given value is more than one (*) or two (**) standard deviations away from the baseline (Wachter).

Model	Data	Generator	Cost ↓	Unfaithfulness ↓	Implausibility ↓	Redundancy ↑	Uncertainty ↓	Validity ↑	
Circles	JEM	ECCCo	0.74 ± 0.21	0.52 ± 0.36	1.22 ± 0.46	0.00 ± 0.00	0.00 ± 0.00	1.00 ± 0.00	
		ECCCo (no CP)	0.72 ± 0.21	0.54 ± 0.39	1.21 ± 0.46	0.00 ± 0.00	0.00 ± 0.00	1.00 ± 0.00	
		ECCCo (no EBM)	0.52 ± 0.15	0.70 ± 0.33	1.30 ± 0.37	0.00 ± 0.00	0.00 ± 0.00	1.00 ± 0.00	
		REVISE	1.28 ± 0.14	0.33 ± 0.01**	0.64 ± 0.00**	0.00 ± 0.00	0.00 ± 0.00	1.00 ± 0.00	
		Schut	1.06 ± 0.43	0.54 ± 0.43	1.28 ± 0.53	0.26 ± 0.25*	0.00 ± 0.00	1.00 ± 0.00	
		Wachter	0.45 ± 0.15	0.68 ± 0.34	1.33 ± 0.32	0.00 ± 0.00	0.00 ± 0.00	1.00 ± 0.00	
	MLP	ECCCo	0.67 ± 0.19	0.65 ± 0.53	1.17 ± 0.41	0.00 ± 0.00	0.09 ± 0.19**	1.00 ± 0.00	
		ECCCo (no CP)	0.71 ± 0.16	0.49 ± 0.35	1.19 ± 0.44	0.00 ± 0.00	0.05 ± 0.16**	1.00 ± 0.00	
		ECCCo (no EBM)	0.45 ± 0.11	0.84 ± 0.51	1.23 ± 0.31	0.00 ± 0.00	0.15 ± 0.23*	1.00 ± 0.00	
		REVISE	1.24 ± 0.15	0.06 ± 0.01**	0.64 ± 0.00**	0.00 ± 0.00	0.00 ± 0.00**	1.00 ± 0.00	
		Schut	0.57 ± 0.11	0.58 ± 0.37	1.23 ± 0.43	0.43 ± 0.18**	0.00 ± 0.00**	1.00 ± 0.00	
		Wachter	0.40 ± 0.09	0.83 ± 0.50	1.24 ± 0.29	0.00 ± 0.00	0.53 ± 0.01	1.00 ± 0.00	
GMSC	JEM	ECCCo	17.45 ± 2.92**	79.16 ± 11.67**	18.26 ± 4.92**	0.00 ± 0.00	0.10 ± 0.01	1.00 ± 0.00	
		REVISE	3.43 ± 1.67**	186.40 ± 28.06	5.34 ± 2.38**	0.00 ± 0.00	0.51 ± 0.22	1.00 ± 0.00	
		Schut	1.27 ± 0.33**	200.98 ± 28.49	6.50 ± 2.01**	0.77 ± 0.07**	0.07 ± 0.00	1.00 ± 0.00	
		Wachter	57.71 ± 0.47	214.08 ± 45.35	61.04 ± 2.58	0.00 ± 0.00	0.07 ± 0.00	1.00 ± 0.00	
	JEM Ensemble	ECCCo	17.43 ± 3.04**	83.28 ± 13.26**	17.21 ± 4.46**	0.00 ± 0.00	0.16 ± 0.11	1.00 ± 0.00	
		REVISE	2.94 ± 1.13**	194.24 ± 35.41	4.95 ± 1.26**	0.00 ± 0.00	0.51 ± 0.29	1.00 ± 0.00	
		Schut	1.03 ± 0.20**	208.45 ± 34.60	6.12 ± 1.91**	0.85 ± 0.05**	0.09 ± 0.04	1.00 ± 0.00	
		Wachter	56.79 ± 44.68	186.19 ± 33.88	60.70 ± 44.32	0.00 ± 0.00	0.07 ± 0.00	1.00 ± 0.00	
	MLP	ECCCo	17.05 ± 2.87	75.93 ± 14.27**	17.20 ± 3.15	0.00 ± 0.00	0.19 ± 0.08	1.00 ± 0.00	
		REVISE	2.93 ± 1.24*	196.75 ± 41.25	4.84 ± 0.60**	0.00 ± 0.00	0.38 ± 0.18	1.00 ± 0.00	
		Schut	1.49 ± 0.87**	212.00 ± 41.15	6.44 ± 1.34	0.77 ± 0.13**	0.12 ± 0.01	1.00 ± 0.00	
		Wachter	4.48 ± 0.18	184.03 ± 48.16	7.49 ± 0.89	0.00 ± 0.00	0.12 ± 0.00	1.00 ± 0.00	
	MLP Ensemble	ECCCo	16.63 ± 2.62	73.86 ± 14.63**	17.92 ± 4.17	0.00 ± 0.00	0.23 ± 0.07	1.00 ± 0.00	
		REVISE	3.73 ± 2.36	207.21 ± 43.20	5.78 ± 2.10**	0.00 ± 0.00	0.33 ± 0.19	1.00 ± 0.00	
		Schut	1.20 ± 0.47**	205.36 ± 32.11	7.00 ± 2.15*	0.79 ± 0.09**	0.12 ± 0.01	1.00 ± 0.00	
		Wachter	4.97 ± 0.47	177.20 ± 25.86	10.27 ± 3.21	0.00 ± 0.00	0.11 ± 0.00	1.00 ± 0.00	
	Linearly Separable	JEM	ECCCo	0.75 ± 0.17	0.03 ± 0.06**	0.20 ± 0.08**	0.00 ± 0.00	0.00 ± 0.00	1.00 ± 0.00
			ECCCo (no CP)	0.75 ± 0.17	0.03 ± 0.06**	0.20 ± 0.08**	0.00 ± 0.00	0.00 ± 0.00	1.00 ± 0.00
ECCCo (no EBM)			0.70 ± 0.16	0.16 ± 0.11	0.34 ± 0.19	0.00 ± 0.00	0.00 ± 0.00	1.00 ± 0.00	
REVISE			0.41 ± 0.14	0.15 ± 0.00**	0.41 ± 0.01**	0.00 ± 0.00	0.72 ± 0.02	1.00 ± 0.00	
Schut			1.15 ± 0.35	0.39 ± 0.07	0.73 ± 0.17	0.25 ± 0.25	0.00 ± 0.00	1.00 ± 0.00	
Wachter			0.50 ± 0.13	0.18 ± 0.10	0.44 ± 0.17	0.00 ± 0.00	0.00 ± 0.00	1.00 ± 0.00	
MLP		ECCCo	0.95 ± 0.16	0.29 ± 0.05**	0.23 ± 0.06**	0.00 ± 0.00	0.00 ± 0.00**	1.00 ± 0.00	
		ECCCo (no CP)	0.94 ± 0.16	0.29 ± 0.05**	0.23 ± 0.07**	0.00 ± 0.00	0.00 ± 0.00**	1.00 ± 0.00	
		ECCCo (no EBM)	0.60 ± 0.15	0.46 ± 0.05	0.28 ± 0.04**	0.00 ± 0.00	0.02 ± 0.10**	1.00 ± 0.00	
		REVISE	0.39 ± 0.15	0.52 ± 0.04	0.41 ± 0.01	0.00 ± 0.00	0.98 ± 0.00	1.00 ± 0.00	
		Schut	0.77 ± 0.17	0.43 ± 0.06*	0.47 ± 0.36	0.20 ± 0.25	0.00 ± 0.00**	1.00 ± 0.00	
		Wachter	0.51 ± 0.15	0.51 ± 0.04	0.40 ± 0.08	0.00 ± 0.00	0.59 ± 0.02	1.00 ± 0.00	
MNIST		JEM	ECCCo	334.98 ± 46.54	19.27 ± 5.02**	314.54 ± 32.54*	0.00 ± 0.00	4.50 ± 0.00**	1.00 ± 0.00
			REVISE	170.06 ± 62.45	188.54 ± 26.22*	254.32 ± 41.55**	0.00 ± 0.00	4.57 ± 0.14	1.00 ± 0.00
			Schut	7.63 ± 2.55**	199.70 ± 28.43	273.01 ± 39.60**	0.99 ± 0.00**	4.56 ± 0.13	1.00 ± 0.00
			Wachter	128.13 ± 14.81	222.81 ± 26.22	361.38 ± 39.55	0.00 ± 0.00	4.58 ± 0.16	1.00 ± 0.00
		JEM Ensemble	ECCCo	342.64 ± 41.14	15.99 ± 3.06**	294.72 ± 30.75**	0.00 ± 0.00	2.07 ± 0.06**	1.00 ± 0.00
			REVISE	171.95 ± 58.81	173.05 ± 20.38**	246.20 ± 37.74**	0.00 ± 0.00	2.76 ± 0.45	1.00 ± 0.00
	Schut		7.96 ± 2.49**	186.91 ± 22.98*	264.68 ± 37.58**	0.99 ± 0.00**	3.02 ± 0.26	1.00 ± 0.00	
	Wachter		134.98 ± 16.95	217.37 ± 23.93	362.91 ± 39.40	0.00 ± 0.00	3.10 ± 0.31	1.00 ± 0.00	
	MLP	ECCCo	605.17 ± 44.78	41.95 ± 6.50**	591.58 ± 36.24	0.00 ± 0.00	0.57 ± 0.00**	1.00 ± 0.00	
		REVISE	146.76 ± 37.07	365.69 ± 14.90*	245.36 ± 39.69**	0.00 ± 0.00	0.72 ± 0.18	1.00 ± 0.00	
		Schut	9.25 ± 1.31**	371.12 ± 19.99	245.11 ± 35.72**	0.99 ± 0.00**	0.75 ± 0.23	1.00 ± 0.00	
		Wachter	135.08 ± 15.68	384.76 ± 16.52	359.21 ± 42.03	0.00 ± 0.00	0.81 ± 0.22	1.00 ± 0.00	
MLP Ensemble	ECCCo	525.87 ± 34.00	31.43 ± 3.91**	490.88 ± 27.19	0.00 ± 0.00	0.29 ± 0.00**	1.00 ± 0.00		
	REVISE	146.38 ± 35.18	337.21 ± 11.68*	244.84 ± 37.17**	0.00 ± 0.00	0.45 ± 0.16	1.00 ± 0.00		
	Schut	9.75 ± 1.00**	344.60 ± 13.64*	252.53 ± 37.92**	0.99 ± 0.00**	0.55 ± 0.21	1.00 ± 0.00		
	Wachter	134.48 ± 17.69	358.51 ± 13.18	352.63 ± 39.93	0.00 ± 0.00	0.58 ± 0.67	1.00 ± 0.00		
Moons	JEM	ECCCo	1.56 ± 0.44	0.31 ± 0.30*	1.20 ± 0.15**	0.00 ± 0.00	0.00 ± 0.00**	1.00 ± 0.00	
		ECCCo (no CP)	1.56 ± 0.46	0.37 ± 0.30*	1.21 ± 0.17**	0.00 ± 0.00	0.00 ± 0.00**	1.00 ± 0.00	
		ECCCo (no EBM)	0.80 ± 0.25	0.91 ± 0.32	1.71 ± 0.25	0.00 ± 0.00	0.00 ± 0.00**	1.00 ± 0.00	
		REVISE	1.04 ± 0.43	0.78 ± 0.23	1.57 ± 0.26	0.00 ± 0.00	0.00 ± 0.00**	1.00 ± 0.00	
		Schut	1.13 ± 0.29	0.66 ± 0.25	1.47 ± 0.10**	0.07 ± 0.18	0.00 ± 0.00**	1.00 ± 0.00	
		Wachter	0.73 ± 0.24	0.78 ± 0.23	1.75 ± 0.19	0.00 ± 0.00	0.02 ± 0.11	1.00 ± 0.00	
	MLP	ECCCo	2.18 ± 1.05	0.80 ± 0.62	1.69 ± 0.40	0.00 ± 0.00	0.15 ± 0.24*	1.00 ± 0.00	
		ECCCo (no CP)	2.07 ± 1.15	0.79 ± 0.62	1.68 ± 0.42	0.00 ± 0.00	0.15 ± 0.24*	1.00 ± 0.00	
		ECCCo (no EBM)	1.25 ± 0.92	1.34 ± 0.47	1.68 ± 0.47	0.00 ± 0.00	0.43 ± 0.18	1.00 ± 0.00	
		REVISE	0.79 ± 0.19*	1.45 ± 0.44	1.64 ± 0.31	0.00 ± 0.00	0.40 ± 0.22	1.00 ± 0.00	
		Schut	0.78 ± 0.17*	1.39 ± 0.50	1.59 ± 0.26	0.28 ± 0.25*	0.00 ± 0.00**	1.00 ± 0.00	
		Wachter	1.08 ± 0.83	1.32 ± 0.41	1.69 ± 0.32	0.00 ± 0.00	0.52 ± 0.08	1.00 ± 0.00	




Figure 6: Counterfactuals for *MNIST* data and our *JEM Ensemble*. Original images are shown on the diagonal with the corresponding counterfactuals plotted across rows.